

Mobile Generator

WSP8



- All steel construction
- Light and sturdy design
- Durable powder-coat finish
- Dual 2 1/2" pintle 2" ball tow hitch
- Torsion axle, wide wheel base

- All aluminum heavy-duty radiator
- 50 gal. heavy-duty steel fuel tank, large filler neck, electric fuel pump
- Standard fork pockets and pick point
- Bolt-on fenders for easy replacement
- Optional equipment: Sound attenuation, Arctic package (block, oil pan and battery Heaters), Manual emergency shut-off device, Extended life oil filtration system, Spare tire with mounting kit, axle locking bar

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Казахстан (772)734-952-31

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Versatile power for the job site

Specifications

Model number	WSP8 / WSP8T - three phase
Standby rating	7.2 kW @ 1 power factor
Prime rating	8.0 kW @ 1 power factor
Frequency/Phase	60 HZ/single or three
Alternator	Mecc Alte
Voltage	120/240 or 120/208 or 277/480
Amperage	
@120/240 1 phase	66.7/33.3 A
@120/208 3 phase	22.2 A
@277/480 3 phase	9.6 A
Engine model	Kubota D1105
HP	13.6
Engine type	1800 RPM, 3 cylinder, 4 cycle
Emission certification	Tier 4 final
Battery	12VC, 550 CCA
Fuel tank capacity	50 gal. (190 L)
Fuel consumption @50% load	110 hours
Control Panel	Hour meter
	Receptacles (varies based on voltage required)
	Circuit breakers
	Fuel gauge
Sound Level @ 23ft (7m)	71 dBA
Dimensions, L x W x H	133 x 55 x 59" (338 x 140 x 150cm)
Dry Weight	1300 lbs. (590kg)
2 year/2000 hour warranty (whichever comes first)	

Wanco’s WSP8 Mobile Generators are the ideal choice when you need to have a reliable power source.

Unsurpassed quality, engineering and value, paired with a multitude of features and options, make this generator perfect for a wide variety of applications.



WSP8 model Control Panel
(Located inside)

Steady power even when wet

Wanco® WAB-Series generators are perfect for pressure washing and other wet applications.

Reliable and long-lasting, these water-resistant generators will do the job now and for years to come. Our brushless design, internal sealants and oversized windings are the perfect platform for these durable, wet area belt-drive generators.

For more than 30 years the Wanco brand has stood for quality and reliability. Learn more at voltmaster.com.



Belt-drive generators for wet applications

- Water resistant
- Bidirectional rotation
- Balanced 120-volt, 20-amp receptacle
- Brushless design with capacitors
- Built-in voltage meter
- Heavy-duty die-cast housing
- Designed for horizontal operation
- Variable voltages available
- Assembled in the United States

				
	WAB35T	WAB45T	WAB55T	WAB65T
AC voltage	120 V	120 V	120 V	120 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz
Max. output	4,000 W	5,000 W	5,500 W	6,500 W
Rated output	3,500 W	4,500 W	5,000 W	6,000 W
Rated current	20 A	20 A	20 A	20 A
Shaft diameter	24 mm	24 mm	24 mm	24 mm
Keyway	8 mm	8 mm	8 mm	8 mm
Connection	4-wire	4-wire	4-wire	4-wire
Minimum engine power	8 hp	9 hp	10 hp	11 hp
Minimum required torque	7.5 ft lbf (10.2 Nm)	7.5 ft lbf (10.2 Nm)	7.5 ft lbf (10.2 Nm)	7.5 ft lbf (10.2 Nm)
Required RPM	3600	3600	3600	3600
Dimensions, L × W × H	16½ × 8½ × 10½" (42 × 22 × 27cm)	16½ × 8½ × 10½" (42 × 22 × 27cm)	16½ × 8½ × 10½" (42 × 22 × 27cm)	16½ × 8½ × 10½" (42 × 22 × 27cm)
Dry weight	69 lbs. (31kg)	72 lbs. (33kg)	74 lbs. (34kg)	76 lbs. (35kg)
Receptacles	120Vac 20A duplex	120Vac 20A duplex	120Vac 20A duplex	120Vac 20A duplex
Optional accessories	Winco® adapter plate	Winco adapter plate	Winco adapter plate	Winco adapter plate

Interior bolts sealed with Loctite® Threadlocker Blue 242® or equivalent. Pulley and belt not included.



Portable Gas Generators

Extremely durable and dependable, every model features simple operation and ease of service. Users and commercial rental centers alike can trust the quality of these generators to give many years of reliable performance.

- 100% copper windings
- Kohler® Command PRO® OHV engines
- AVR (automatic voltage regulator)
- Large capacity fuel tank with fuel gauge
- GFCI receptacles
- Hour meter
- Wheel kit with flat free tires and folding handles
- 3-year warranty



Specifications



Model	WGC3800	WGC5300	WGC7500E
Emissions Compliancy	EPA, CARB	EPA, CARB	EPA, CARB
Type	Brush Type	Brush Type	Brush Type
Voltage Regulation	AVR	AVR	AVR
Frequency/Phase	60 Hz/Single	60 Hz/Single	60 Hz/Single
Voltage	120/240	120/240	120/240
Max Output	3800 Watt	5300 Watt	7500 Watt
Max Amps	31.7/15.8	44.2/22.1	62.5/31.2
Rated Output	3500 Watt	4800 Watt	7000 Watt
Rated Amps	29.2/14.6	40/20	58.3/29.2
Sound Level @ 23ft (7m)	72 dBA	72 dBA	76 dBA
Current Protection	Dual Pole Magnetic Circuit Breaker & GFCI	Dual Pole Magnetic Circuit Breaker & GFCI	Dual Pole Magnetic & Thermal Circuit Breaker & GFCI
OHV Engine	Kohler CH270-3056	Kohler CH395-3056	Kohler CH440-3129
Low Oil System	Low Oil Shutdown	Low Oil Shutdown	Low Oil Shutdown
Fuel Tank Capacity	4 gal. (15L)	8 gal. (30L)	8 gal. (30L)
Hours at Rated Load	5.9	8.6	5.9
Hours at 50% Rated Load	11.8	17.4	11.8
Starting System	Recoil	Recoil	Electric with Recoil Backup
Battery Included - Battery Replacement or equal	N/A	N/A	Sealed 12 V 18 Ahr Interstate BSL1116
Dimensions with wheel kit, handles folded down (L×W×H)	27×25×26 in. (67×64×66cm)	30×29×29 in. (76×74×74cm)	30×29×29 in. (76×74×74cm)
Dimensions without wheel kit (L×W×H)	25×17×20" (64×43×51cm)	28×21×24" (71×53×61cm)	28×21×24" (71×53×61cm)
Dry Weight (includes wheel kit)	137 lbs. (62kg)	215 lbs. (98kg)	227 lbs. (103kg)
GFCI 120V 20 Amp. Duplex	2	2	2
120V 30 Amp. Twist Lock	N/A	1	1
120/240V 30 Amp. Twist Lock	1	1	1
Hour Meter	Yes	Yes	Yes
Wheel Kit	Yes	Yes	Yes

Mobile Generators

Trailers & Skid-Mounted

- Robust rental-grade construction
- Heavy-duty, 4-cycle, EPA-certified Flex diesel engines
- Enlarged fuel cell for maximum run times
- Oversized alternator with PMG for superior starting
- Heavy gauge, powder-coated, lockable enclosure
- Dual-containment fuel cell and environmental containment basin
- Sound attenuation for superior noise reduction
- Voltage adjusting rheostat
- Emergency stop button
- Multi-voltage switch
- Lifting eye
- Deep Sea 7000-Series controllers
- Available with or without trailer
- 2-year/2000-hour warranty



Model	WSP12-1	WSP25	WSP40	WSP70	WSP80	WSP100	WSP125
Standby Rating	11.9 kW / 18.8 hp	27 kVA / 20 kW	38 kVA / 32 kW	69 kVA / 56 kW	83 kVA / 64 kW	101 kVA / 80 kW	123 kVA / 100 kW
Prime Rating	11.9 kW / 18.8 hp	25 kVA / 18 kW	35 kVA / 29 kW	63 kVA / 50 kW	75 kVA / 58 kW	93 kVA / 72 kW	112 kVA / 90 kW
Voltages	120/240	120/240	120/240	120/240	120/240	120/240	120/240
		120/208	120/208	120/208	120/208	120/208	120/208
		277/480	277/480	277/480	277/480	277/480	277/480
Engine Model	Perkins 403F-15G	Perkins 404D-22G	Perkins 404D-22TAG	Perkins 1104D-44TG1	Perkins 1104D-E44TG1	Perkins 1104D-E44TAG1/2	Perkins 1104D-E44TAG2
Engine Type	4-cycle indirect injection diesel	4-cycle indirect injection diesel	4-cycle indirect injection diesel	4-cycle direct injection turbo-charged diesel	4-cycle direct injection turbo-charged diesel	4-cycle direct injection turbo-charged diesel	4-cycle direct injection turbo-charged diesel
Alternator	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte
Emissions Certification*	Tier 4 Final	Tier 4i Flex	Tier 4i Flex	Tier 3 Flex	Tier 3 Flex	Tier 3 Flex	Tier 3 Flex
Fuel Tank Capacity	60.7 gal (230 L)	60.7 gal (230 L)	60.7 gal (230 L)	124 gal (470 L)	124 gal (470 L)	158 gal (600 L)	177 gal (670 L)
Continuous Run Time							
@ 25% load	291.0 hr	101.2 hr	55.2 hr	88.6 hr	51.7 hr	56.4 hr	47.8 hr
@ 50% load	83.1 hr	60.7 hr	46.7 hr	53.9 hr	38.8 hr	45.1 hr	42.1 hr
@ 75% load	58.2 hr	50.6 hr	22.5 hr	36.5 hr	27.6 hr	32.2 hr	30.5 hr
@ 100% load	48.5 hr	38.0 hr	25.3 hr	25.3 hr	24.3 hr	25.5 hr	23.3 hr
Standby Current							
@ 120/240V, 1-phase	25 A	54 A	88 A	154 A	175 A	217 A	275 A
@ 120/240V, 3-phase	—	60 A	96 A	168 A	192 A	241 A	301 A
@ 120/208V, 3-phase	—	69 A	111 A	195 A	222 A	278 A	347 A
@ 277/480V, 3-phase	—	30 A	48 A	84 A	96 A	120 A	150 A
Sound Level @ 23ft (7m)	59 dBA	59 dBA	59 dBA	69 dBA	69 dBA	69 dBA	69 dBA
Dimensions, L x W x H	77 x 32 x 49 in (195 x 80 x 125 cm)	90 x 42 x 62 in (229 x 107 x 158 cm)	90 x 42 x 62 in (229 x 107 x 158 cm)	112 x 44 x 70 in (284 x 112 x 178 cm)	112 x 44 x 70 in (284 x 112 x 178 cm)	120 x 44 x 77 in (304 x 112 x 196 cm)	120 x 44 x 77 in (304 x 110 x 196 cm)
Dry Weight	2020 lb (918 kg)	2920 lb (1324 kg)	4025 lb (1826 kg)	4400 lb (1996 kg)	4620 lb (1996 kg)	4840 lb (2195 kg)	5060 lb (2295 kg)
Dimensions with Trailer, L x W x H	155 x 55 x 73 in (393 x 139 x 186 cm)	154 x 71 x 79 in (391 x 180 x 201 cm)	154 x 71 x 79 in (391 x 180 x 201 cm)	186 x 77 x 87 in (472 x 196 x 221 cm)	186 x 77 x 87 in (472 x 196 x 221 cm)	186 x 77 x 94 in (472 x 196 x 239 cm)	186 x 77 x 94 in (472 x 196 x 239 cm)
Dry Weight with Trailer	2440 lb (1107 kg)	3900 lb (1769 kg)	5000 lb (2268 kg)	5350 lb (2427 kg)	5350 lb (2427 kg)	5570 lb (2527 kg)	5790 lb (2626 kg)

Trailers include all-welded structural steel frame, , with electric brakes (optional on some models), running lights, license plate bracket and ball or pintle hitch.

*Tier 3 Flex and Tier 4i Flex engines are subject to availability. For Tier 4 Final engine availability, contact factory.

Архангельск (8182)63-90-72
 Астана (7172)727-132
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16

Россия (495)268-04-70

Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13

Казахстан (772)734-952-31

Сургут (3462)77-98-35
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93